

7

Referências bibliográficas

- [1] SINCLAIR,I. **Sensors and transducers**. 2ed. Boston. U. Science Books, Salsalito,CA,1982.305p.
- [2] SECO,F. et al. A high accuracy magnetostrictive linear position sensor, **Sensor and actuators**, v.123, p. 216-223, agosto 2005.
- [3] HEALEY.G.W,; MEYDAN,T. Linear Variable differential transformer (LVDT): linear displacement transducer utilizing ferromagnetic amorphous metallic glass ribbons. **Sensors and actuors**. V.30, p.582-587. 1992.
- [4] HRISTOFOROU,E. et al. On the calibration of position sensors based on magnetic delay lines. **Sensors and actuors**. v.59, p.89-93.1997.
- [5] KARAGIANNIS,V; MANASIS,C; BARGIOTAS,D. Position sensors based on the delay line principle. **Sensors and actuors**. v.106, p.183-186. 2003.
- [6] CHIRIAC,H; MARINESCU,C.S. New position sensor based on ultraacoustic standing waves in FeSiB amorphous wires. **Sensors and actuors**, v.81, p.174-175. 2000.
- [7] HANDLEY,R. **Modern magnetic materials. Principles and applications**.New York, Jhon Wiley & Sons, Inc, 2000.740p.
- [8] CRAIK, D. **Magnetism, principles and aaplications**. New York, Jhon Wiley & Sons, Inc,1995.459p.
- [9] CALKINS,F.T; FLATAU,A.B. 15th National Conference on Noise Control Engineering, Iowa State University.1997. Disponível em <http://www.aerosmart.umd.edu/TechPubs/calkins>. Acesso em 20 de mar. 2006.
- [10] BOHN, F. Magnetostricção e ruído Barkhausen em aços elétricos de grão não-orientado. Santa Maria. 2005. Dissertação de mestrado. Universidade Federal de Santa Maria.
- [11] ASSIS.B.G. Caracterização de ímãs por meio da visualização dos domínios magnéticos. **Revista Brasileira de Física**, vol.20, n2, junho. 1998.
- [12] CHEN,D.X, SANCHEZ,A. Demagnetizing factors for rectangular prism. **IEEE Transacations on magnetics**, vol.41, n.6, junho. 2005.
- [13] CRAIK, D.J. Demagnetizing fields in uniformly magnetized retangular prismatic crystals. **Journal appy.Phys**, v.18.1967.

- [14] [33] DAPINO, J. On magnetostrictive materials and their use in smart materialas transducers.. <http://www.mecheng.osu.edu/~dapino/article.pdf>. Acesso em 25 de abr. 2006
- [15] ENGDAHL, G. **Handbook of Giant Magnetostrictive Materials**. San Diego, Academic Press, 2000. 386p.
- [16] ETREMA, Products, ing, <http://www.etrema-usa.com>. Acesso em 7 de jun.2006.
- [17] SOSHIN, C. **Physics of magnetism**. 2.ed. New York. Jhon Wiley & Sons, Inc, 1964. 554p.
- [18] TX-GMM, Gansu Tianxing Rare Earth Functional Materials Co. Ltd., <http://www.txre.net>. Acesso em 13 de mai. 2006.
- [19] MORA, J. et al. A magnetostrictive sensor interrogated by fiber Gratings for DC-current and temperature discrimination. **IEE photonics tecnology letters**, v,12. n.12, dezembro 2000.
- [20] MOORE, J; ENNIS, M.G. Design of a Terfenol-D based Fiber-optic current transducer. **IEEE Sensors Journal**, v.5, n.5, outubro. 2005.
- [21] CARVALHO, H.R. et al. Remote magnetostrictive position sensors interrogated by fiber Bragg gratings. **Sensors and actuators**, v.135, p.141-145, março. 2007.
- [22] OTHONS, A, KALLY, K. **Fiber Bragg Grattings, Fundamentals and applications in telecommunications and sensing**. Boston. Artech House Publishers. 1999.
- [23] SECO, F. Hysteresis Compensation in a Magnetostrictive Linear Position sensor. **Sensors and actuators**, v.110, p.247-253. 2004.
- [24] National instruments. <http://www.ni.com>. Acesso em 7 de abr. 2006.
- [25] YAMAMOTO, K; NAKANO, H; YAMASHIRO, Y. Effect of compressive stress on hysteresis loss of Terfenol-D. **Journal of magnetism and magnetic materiais**. V.255, p.222-224. 2003.
- [26] MOFFETT, M. et al. Characterization of Terfenol-D for magnetostrictive transducers. **J.Acoust.Soc.Am**, v.89, n.3, p.1448-1455, novembro. 1990.
- [27] YONNET, E.P. Permanent Magnet Bearings and Couplings. **IEEE Transacations on magnetics**, v.17, n.1, p.1169-1173, janerio 1981.
- [28] RIBEIRO, A; S. et al. Comparação entre extensômetro óptico e extensômetro elétrico. **Sociedade Brasileira de Metrologia**, Pernambuco-Brasil, setembro. 2003.
- [29] KITTEL, C. **Introduction to Solid State Physics**. 2ed. New York. Jhon Wiley & Sons, Inc, 1984. 808p.

- [30] TAYLOR, J. **An introduction to error analysis**. 2ed. California. University Science Books. 1997. 327p.
- [31] REITZ, J, MILFORD, F, CHRISTHY, W, Fundamentos de la teoria electromagnetica. 4ed. Mexico. Addison-Wesley Iberoamericana, S.A.
- [32] BRINDLEY, K. **Sensors and transducers**. Great Britanian. Redwood Burn Ltda. 1988. 180p.
- [33] NUSSBAUM, A. Comportamento eletrônico e magnético dos materiais. São Paulo. Editora Edgar Blucher Ltda. 1973. 160p.
- [34] CHAKRABORTY, S; TOMLINSON, G.R. An initial experimental investigation into the change in magnetic induction of a Terfenol-D rod to external stress. **Smarts materials and structures**. V.12, p.763-768., setembro. 2003.
- [35] DAPINO, M. et al. Statistical analysis of Terfenol-D material properties. **Journal of intelligent material systems and structures**, v.17, p.587-599, julho. 2006.
- [36] SATPATHI, D. et al. Design of a Terfenol-D based Fiber Optic current transducer. **IEE Sensors Journal**, v.5, n.5, outubro. 2005.
- [37] MILLER, M.M. et al. Novel absolute displacement sensor utilizing giant magnetoresistance elements. **Journal of Appl. Physics**, v81, n.8, p.4284-4286, abril. 1997.
- [38] ZHOU, Y; SHIN, F.G; Modeling of magnetostriction in particulate composite materials. **IEE Transactions on magnetics**, v41, n.6, junho. 2005.
- [39] CAZO, R.M. et al. Sensor de deformação usando grades de Bragg, **Revista científica telecomunicaciones**, v.3, n.2, dezembro. 2000.
- [40] HRISTOFOROU, E; REILLY, E. Displacement sensors using soft magnetostrictive alloys. **EE Transactions on magnetics**, v.30, n.5, setembro. 1994.
- [41] AFFANI, A. et al. Design and Characterization of Magnetostrictive Linear Displacement Sensors. V.1, p.206-209, maio. 2004.
- [42] YAO, S.X. et al. A study on the wave generation principle of the magnetostrictive linear position sensor. **IEEE International Magnetics Conference**. 1999.